

MPPT 60 150 solar charge controller

MPPT multi-stage charging, better battery life

The MPPT 60 150 is a photovoltaic (PV) charge controller that tracks the maximum power point of a PV array to deliver the maximum available current for charging batteries. When charging, the MPPT 60 150 regulates battery voltage and output current based on the amount of energy available from the PV array and state-of-charge of the battery.

Why choose MPPT 60 150?



True bankability

- Warranty from a trusted partner with over 177 years of experience
- World leader in industrial power drives, UPS and electrical distribution
- Strong service infrastructure worldwide to support your global needs



Higher return on investment

- Maximum Power Point Tracking (MPPT) algorithm continually seeks the maximum power available from the PV array
- Improve battery life with selectable multi-stage temperature compensated charging
- Five-year standard warranty



Flexible

- Stand-alone application or full integration with Conext XW and Conext SW inverter charger system
- Compatible with any brand of PV Module
- Available remote monitoring and configuration



Easy to install

- Configurable auxiliary output
- LCD screen with face plate buttons for configuration and system monitoring
- Integrated PV ground fault protection for negative grounded arrays



Product applications



Residential, backup power and grid-tie



Off-grid solar



Community electrification

| | |
|---------------------------------------|---|
| Device short name | MPPT 60 150 |
| Electrical specifications | |
| Nominal battery voltage | 12, 24, 36, 48, 60 V |
| Battery voltage operating range | 0 Vdc to 80 Vdc |
| Max. PV array voltage (operating) | 140 V |
| Max. PV array open circuit voltage | 150 V including temperature correction factor |
| Max. array short-circuit current | 60 A (48 A @ STC) |
| Max. charge current | 60 A (for all battery voltages except 60 V) |
| Max. and min. wire size in conduit | #6 AWG to #14 AWG (10 to 2.5 mm ²) |
| Max. output power | 3500 W |
| Charger regulation method | Three-stage (bulk, absorption, float) plus manual equalization Two-stage (bulk, absorption) plus manual equalization |
| Supported battery types | Flooded, GEL, AGM, Custom |
| Efficiency | |
| Max. power conversion efficiency | 93% (nominal 12 V), 96% (nominal 24 V), 97% (nominal 36 V), 98% (nominal 48 V), 99% (nominal 60 V) |
| General specifications | |
| Power consumption, night time | 2.5 W |
| Battery temperature sensor | Included |
| Auxiliary output | 5 - 13 V, up to 200 mA |
| Enclosure material | Indoor, ventilated, sheet metal chassis with 2.2 cm and 2.8 cm (7/8 in and 1 in) knockouts and aluminium heat-sink |
| IP degree of protection | IP20 |
| Product weight | 4.8 kg (10.8 lb) |
| Shipping weight | 8.0 kg (17.6 lb) |
| Product dimensions (H x W x D) | 36.8 x 14.6 x 13.8 cm (14.5 x 5.8 x 5.5 in) |
| Shipping dimensions (H x W x D) | 48.3 x 22.9 x 35 cm (19.0 x 9.0 x 9.8 in) |
| Device mounting | Vertical wall mount |
| Ambient air temperature for operation | -20°C to 45°C (-4°F to 113°F) |
| Storage temperature range | -40°C to 85°C (-40°F to 185°F) full power, power derating above 45°C |
| Operating altitude | Sea level to 2000 m (6562 ft) |
| System network and remote monitoring | Available |
| Warranty | Five-year standard |
| Part number | 865-1030-1 |
| Features | |
| Display type | LCD, 2 lines 16 digits |
| Regulatory approval | |
| Safety | CSA Certified (UL1741, CSA 107.1) and CE Marked for the Low Voltage Directive (EN50178) |
| EMC | FCC and Industry Canada (Class B), CE Marked for the EMC Directive (EN61000-6-1, -6-3), C-Tick compliant |

Specifications are subject to change without notice.

MPPT 60 150 solar charge controller works with the following Schneider Electric products

**Conext XW inverter/charger
(230 V/50 Hz)**



XW 4024 Product no. 865-1045-61
XW 4548 Product no. 865-1040-61
XW 6048 Product no. 865-1035-61
(120/240 V/60 Hz)
XW 4024 Product no. 865-1010
XW 4548 Product no. 865-1005
XW 6048 Product no. 865-1000-01



Conext SW inverter/charger

SW 2524 120 Product no. 865-2524
SW 4024 120 Product no. 865-3524
SW 2524 230 Product no. 865-2524-61
SW 4024 230 Product no. 865-3524-61



System Control Panel (SCP)
Product no. 865-1050



Automatic Generator Start (AGS)
Product no. 865-1060



**Conext Combox
Communication device**
Product no. 865-1058